

IMPROVED FLASHLIGHTPRIORITY

This application claims priority to U. S. Application Serial No. 60/224,313 filed
5 August 10, 2000 and entitled, "Flashlight", which is incorporated herein by reference.

FIELD OF INVENTION

The present invention relates to the field of portable, battery-operated flashlights.
More particularly, the present invention relates to a portable, battery-operated flashlight
10 having improved pivoting features such that it may be worn as a head lamp. In another
aspect of the invention, the portable, battery-operated flashlight has improved switching
and focusing features such that the lamp's position in the reflector may be varied to focus
or defocus the light from the lamp.

BACKGROUND OF INVENTION

Flashlights generally include a battery chamber for retaining one or more
batteries, a light bulb electrically connected to the one or more batteries, and a reflector
for reflecting the light from the light bulb in a particular direction. The electrical
connection between the batteries and the light bulb usually includes a switch mechanism
15 for selectively providing electrical energy from the batteries to the light bulb and,
20 therefore, enabling the flashlight to be turned on and off.

A primary function of flashlights is to provide a convenient portable, storable light source that is capable of projecting light in a particular direction. However, it is difficult in some flashlights to project light in a particular direction because of the stationary nature and fixed connectivity of flashlight parts relative to each other. In addition, the difficulty of light projection in a desired direction may be also limited by the inflexible nature of the reflector.

SUMMARY OF INVENTION

The present invention satisfies, to a great extent, the foregoing and other needs not currently satisfied by existing flashlights. This result is achieved, in an exemplary embodiment, by a portable, battery-operated flashlight having an improved pivot point for the lamp portion. In this embodiment, the flashlight takes the form of an attachment usable as a head worn lamp, which may be attached to head gear such as a safety helmet or include an elastic band to secure the flashlight to a user's head.

The flashlight comprises a body, a base portion and a lamp. The body is for retaining at least one battery, and has a serrated-like surface on an exterior surface to facilitate desired angular adjustment of the body, and thus the light. Preferably, the body comprises a top portion and a bottom portion, which contains the serrations. The base portion is pivotally connected to the body at two points, and has pivot stops therein to adjust the body angularly as desired. Preferably, the base portion is affixable to a head gear. The lamp is removably attached to the body, and selectively connected to the battery to cause the lamp to emanate light.

The pivot connection between the base portion and the body allows a low profile positioning of the lamp with respect to a user's desired line of lighted vision. The pivot connection allows for 180 degree angular adjustment of the body and lamp with respect to the base portion. The pivot stops located on the base portion also allow for 180 degree angular adjustment of the body with respect to the base portion. This is achieved when the pivot stops mate with the serrated edges on the body.

In another aspect of the invention, a flashlight having improved switching and focusing features is disclosed. Here, the portable, battery-operated flashlight takes the form of a long-handled flashlight which construction allows variation in the ability to focus and defocus the lamp's light. The flashlight comprises a body, lamp, head assembly and switching assembly. The body retains at least one battery. The lamp, which is removably attached to the body, is selectively connected to the battery to cause the lamp to emanate light. The switching assembly is movable relative to the head assembly such that axial movement of the switching assembly causes electrical coupling of the lamp with the battery and causes a position of the lamp to vary to focus and defocus the light.

The head assembly comprises a bezel that is capable of radial movement to cause the switching assembly to move axially. In this regard, the switching assembly includes a first spring located most adjacent to the battery, and a second spring located most adjacent to the reflector. As the switching assembly moves axially, the first spring is caused to compress first to cause electrical coupling of the lamp with the battery. Once the switch assembly makes electrical contact with the battery, the second spring

compresses to cause the position of the lamp to vary within the reflector to cause focusing and defocusing of the light emanating from the lamp.

With these and other advantages and features of the invention that may become hereinafter apparent, the nature of the invention may be more clearly understood by
5 reference to the following detailed description of the invention, the appended claims and to the several drawings attached herein.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a perspective front view of a head worn flashlight in accordance with an
10 exemplary embodiment of the present invention.

Fig. 2 is a close up view of a preferred embodiment of the serrations on the body.

Fig. 3 is a close up view of a preferred embodiment of the pivot stop on the base.

Fig. 4 is an exploded view of the pivot connection in accordance with the present
invention.

15 Fig. 5 is another view of the flashlight of the present invention.

Fig. 6 is a view showing the removed body of the flashlight.

Fig. 7 is cross-sectional front view of a long-handled flashlight (without bezel) showing readiness of the reflector to move in the direction towards the batteries.

Fig. 8 is cross-sectional front view of a long-handled flashlight (with bezel)
20 showing readiness of the reflector to move in the direction towards the batteries.

Fig. 9 is a cross-sectional front view of the flashlight of Fig. 7 showing the switching assembly is in the "on" position.

Fig. 10 is a cross-sectional front view of the flashlight of Fig. 8 showing the switching assembly is in the "on" position.

Fig. 11 is a cross-sectional front view of the flashlight of Fig. 7 showing compression of the second spring.

5 Fig. 12 is a cross-sectional front view of the flashlight of Fig. 8 showing compression of the second spring.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

Referring now to the figures, wherein like reference numerals indicate like
10 elements, in Fig. 1 there is shown a perspective front view of a head worn flashlight 10 in accordance with an exemplary embodiment of the present invention. As depicted, flashlight 10 is shown as having a head assembly 12, a body 14 and a base 16, which may serve as an attachment portion. The head assembly 12 and body 14 generally comprise the head light 20.

15 The head assembly 12 comprises a bezel 13, a switch assembly (not shown), a lamp (not shown), reflector (not shown) and lens 15. In this embodiment, the bezel 13 is capable of radial movement (i.e., rotation) to cause the switch to selectively connect the lamp to the one or more batteries, and therefore cause the lamp to emanate light. Further, the bezel 13 is capable of radial movement to cause focusing and defocusing of light
20 from the lamp. The reflector directs light from the lamp through the lens. The head light 20 of the flashlight 10 is assembled by attaching the head assembly 12 and switch assembly to the body 14, such that the lamp is positioned in the switch assembly and is in

alignment with the reflector via an opening in the reflector. The head assembly 12 is removably attached to the body 14.

The body 14 serves as a chamber for holding one or more batteries in a series arrangement. The body 14 comprises a top portion 24 and a bottom portion 26. The top portion 24 is removably attached to the bottom portion 26 to selectively uncover the interior portion of the body 14 to allow, among other things, the one or more batteries to be inserted or removed. Referring to Figs. 1 and 2, the body 14 also includes, in a mid-region of the bottom portion 26, serrations 28 on an exterior surface of the body 14 for engaging a surface 30 of the base 16. A close-up view of a preferred embodiment of serrations 28 is shown in Fig. 2. Serrations 28 facilitate desired angular adjustment of the body 14 and head assembly 12 with respect to the base 16. This is accomplished when serrations 28 mate with the pivot stop 29 located on base 16, as shown in Fig. 3.

In general, movement of the body 14 is achieved by two pivot connection points 22 at each end of the body 14 to the base 16. The substantially flat, arched undersurface (not shown) of the base 16 facilitates standing of the flashlight 10 on a flat surface. It also facilitates attachment of the base 16 to a curved surface object, such as head gear, or placement directly on a human forehead. In this regard, attachment of the flashlight 10 to a safety helmet, for example, allows desired positioning of the direction of the light emanating from the lamp while providing more stability. Another advantage of the attachment feature of base 16 is hands free use of the flashlight 10.

In the embodiment depicted, the base 16 is rectangular in shape and has an arm 32 projecting from each base end. A distal end 34 of the arm 32 is the location area of the

pivot point 22 connecting the body 14 to the base 16. As shown in Fig. 4, screw 21 engages nut 23 to form pivot point 22. As shown in Fig. 5, use of the serrations 28 in conjunction with pivot point 22 allows for 180 degree angular adjustment of the body 14, and consequently the head light 12, with respect to the base 16. Additionally, when the flashlight 10 is used as a head lamp, the pivot point 22 allows the body 14 to maintain contact with the base 16.

Referring now to Fig. 6, there is shown a view of the flashlight showing removal of the body 14 casing, which covered the batteries 40. In the embodiment depicted, the two batteries 40 are exposed to illustrate that the pivot point 22 is spatially located at a distance 100 from the plane that intersects a center point of each battery. In this regard, the pivot point 22 is located between the batteries and the head assembly 12. Preferably, the pivot point 22 is located substantially along the tangent plane 41 of the two batteries 40. This advantageously facilitates the balanced positioning of the head assembly 12 and comfort for a user wearing the device.

Referring now to Figs. 7-12, there is shown a long-handled flashlight having improved switching and focusing features in accordance with another embodiment of the present invention. It is important to note that the improved switching and focusing features described below and shown in Figs. 7-12 are applicable to the head light 20 described above and shown in Figs. 1-6. As depicted, the flashlight is shown as having a head assembly 62, a body 64 and a switching assembly 65. The head assembly 62 comprises a lamp 68, a reflector 70, a bezel 72, and a lens 73. The switching assembly 65 includes a first spring 66, a second spring 74, a first electrical contact 80 and a second

A1
cont.

electrical contact 82. The lamp 68 (partially shown) includes a first pin 84 that contacts the first electrical contact 80 and a second pin 86 that contacts the second electrical contact 82. The second pin 85 is electrically connected to the first spring 66 that is in electrical contact with one of the batteries 76. The body 64 includes a chamber contact 88 that runs the length of the body 64 and is capable of electrical connection to batteries 76 located within the body 64. A description of the switching, focusing and defocusing aspects of the flashlight is explained below with reference to Figs. 7 - 12.

Referring to Figs. 7 and 8, the flashlight is shown in the "off" position. In this position, the switching assembly 65 is permitted to move towards and away from the body 64 (i.e. axially). Axial movement of the switching assembly 65 is achieved by radial movement of the bezel 72. In this regard, the bezel 72 is capable of radial movement that causes the bezel 72 to move axially towards the battery 76. The bezel 72 is in contact with the reflector 70, and the reflector is in contact with the second spring 74. As a result of radial movement of the bezel 72, the reflector 70 moves axially towards the battery 76.

A2 Referring now to Figs. 9 and 10, the flashlight is shown in the "on" position. Noteworthy is the collapsed position of the first spring 66. The second spring 74 is not collapsed. This is accomplished by turning or rotating the bezel 72. As the bezel is rotated, the reflector 70 is caused to axially move towards the battery 76. The compression force of the first spring 66 and the second spring 74 are selected to allow the first spring 66 to substantially collapse before the second spring 74. As a result, as the bezel 72 is rotated, the reflector 70 exerts a downward axial compressive force, causing the first

A2
correl.

spring 66 only to collapse. At this juncture, the second spring 74 does not collapse during this movement and, as a result, the reflector 70 and the switching assembly move together towards the batteries 76. The compression of the first spring 66 causes the lamp 68 to turn on because an electrical connection is made with the batteries 76. In this regard, the first electrically contact 80 contacts the chamber contact 88 causing a completion of the electrical connection between the first pin 84 and second pin 88 and the batteries 76.

A3

Referring now to Figs. 11 and 12, there is shown the collapsed position of both the first spring 66 and the second spring 74. When the first electrically contact 80 contacts the chamber contact 88, and the bezel continues to rotate, further movement of the reflector 70 exerts additional compressive forces in the direction of the batteries 76, causing the second spring 74 to collapse. As a consequence, the reflector 70 is caused to move relative to the lamp 68 and the switching assembly. In other words, the practical effect of this condition is that the position of the lamp 68 within the reflector 70 can be varied as desired to focus or defocus the light from the lamp 68 through the lens 73, depending on where the lamp 68 is positioned within the reflector 70.

The head portion of the flashlight can be disassembled by rotating the bezel 72 from the "off" position in a direction opposite to the first rotation direction, thereby disengaging the second spring 74 and then the first spring 66 from electrical contact.

The foregoing description of the present invention has been presented for purposes of illustration and description. The description is not intended to limit the invention to the form disclosed herein. Consequently, the invention and modifications

Year	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100
1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	